

TECHNICAL DATA SHEET

INSTRUMENTATION CABLES – MAS SERIES


OVERALL SCREEN

MAS5404CS – 4 Pair 0.75mm² TCW CS

APPLICATION: Instrumentation Cable suitable for Industrial Applications.



Standards	AS/NZS1125 , AS/NZS3808 , IEC 60332-1-2 , IEC 60332-3-22 , IEC 60079.14 , RoHS Compliant
Conductor	Stranded Tinned Copper Conductor 0.75mm (7/0.37mm)
Insulation	0.4mmPVC ,V90HT , White/Black Numbered Pair's
Screen	Overall Shield of Al/Polyester Foil c/w Tinned Copper Drain Wire (7/0.20mm)
Armour	Not Applicable
Sheath	SPVC , 5V-90 , Flame Retardant , UV Resistant Black PVC
Operating Temp.	-20°C to +90°C
Max. Rated Voltage	110VRMS/150VDC
Insulation Voltage Rating	300V
Max. Current Rating	7.5 Amp
Max. DC Resistance @ 20°C	24.5 Ω/km
Max. Capacitance Cond. To Cond. (Screened)	150pf/m
Max. Capacitance Cond. To Scr. (Screened)	250pf/m
Inductance @ 1kHz	0.98 mH/km
L/R Ratio @ 1kHz	20.0 μH/Ω
Insulation Resistance	140 MΩ/km
Bending Radius (Fixed)	10D (D = Cable Diameter)



Product	Pairs	Conductor	Insulation Thickness	Outer Sheath Thickness	Approx Cable O.D	Approx. Cable Weight
Maser Ordering Code	Number of Pairs	mm ²	mm	mm	mm	Kg/km
MAS5404CS	4 Pair	0.75mm	0.40	0.80	9.6	120

Jacket Marking

MASER MAS5404CS INSTRUMENTATION CABLE 4PR 0.75mm² TCW/PVC/CS/PVC V90 UV RoHS (MANUFACTURE DATE) (METRE MARK)

Recommended Gland = MM-A1A2-20S

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.