

1 Core Inductive Traffic Loop Cable XLPE X-90

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



ORDERING CODE	MLDC17050 500M MLDC17050 1000M
CONDUCTOR	Tinned Copper Wire to AS1125 1.5mm (7/0.50) Voltage Rating: 300V Amp Rating @ 30°C: 13 Max. DC Resistance @ 20°C: 13.6 (Ω/km)
INSULATION	X90 XLPE to AS/NZS3191 Colour: Black Thickness: 1.0mm
TEMP. RANGE	-20°C to +90°C
NOMINAL O.D (mm)	4.0mm
PACKAGING	500m Wooden Drum 1000m Wooden Drum

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.