

SPEAKER CABLE

2 Core, Figure 8 Parallel Webbed, OFHC Oxygen Free Plain Copper

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



CONSTRUCTION	0.75mm ²
PRODUCT CODE	MSPK224020 100WY MSPK224020 500WY
CONDUCTOR	Stranded Oxygen Free Plain Copper wire to AS1125 $\varnothing = 24 \times 0.20 + 0.003 \text{ mm}^2$
MAXIMUM D.C RESISTANCE AT 20°C (Ω/KILOMETRE)	26 ohm/km
INSULATION	V-75 PVC (AS/NZS 3808 & RoHS) Colour: White with Yellow Stripe Thickness: 0.8±0.05mm
NOMINAL O.D (mm)	$\varnothing = 2.8 \times 6.0 + 0.10 \text{ mm}$
PACKAGING	100m Plastic Reel 500m Wooden Reel

Maser Communications products are approved and meet the GREENSTAR "Best Practice PVC" criteria as set out by the Green Building Council of Australia (GBCA). BUREAU VERATIS CoC No:2821 7/8/2019.

As part of this commitment to reduce the environmental impact of PVC material, Maser Communications will aid in the process of recycling any of their relevant product that has reached end of life.

For further information on this process please contact us.



Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.