

Pro Series Speaker Cable

2 Core / 4 Core, High Strand, OFHC, Black

100v Audio Cable



CONSTRUCTION	2 Core 1.3mm ²	2 Core 2.1mm ²	4 Core 1.3mm ²	4 Core 2.1mm ²
ORDERING CODE	(100m) MSPK265016 100B (250m) MSPK265016 250B	(100m) MSPK2105016 100B (250m) MSPK2105016 250B	(100m) MSPK465016 100B (250m) MSPK465016 250B	(100m) MSPK4105016 100B (250m) MSPK4105016 250B
CONDUCTOR	1.3mm (16AWG) Ø = 65*0.16 mm*2 Stranded Oxygen Free Plain Copper wire to AS1125	2.1mm (14AWG) Ø = 105*0.16 mm*2 Stranded Oxygen Free Plain Copper wire to AS1125	1.3mm (16AWG) Ø = 65*0.16 mm*4 Stranded Oxygen Free Plain Copper wire to AS1125	2.1mm (14AWG) Ø = 105*0.16 mm*4 Stranded Oxygen Free Plain Copper wire to AS1125
MAXIMUM D.C RESISTANCE AT 20°C (Ω/Km)	13.7 ohm/km	8.6 ohm/km	13.7 ohm/km	8.6 ohm/km
INSULATION	V-75 PVC (AS/NZS 3808 & RoHS) Colour: Red, Black Ø = 2.10±0.05mm mm*2	V-75 PVC (AS/NZS 3808 & RoHS) Colour: Red, Black Ø = 2.65±0.05mm mm*2	V-75 PVC (AS/NZS 3808 & RoHS) Colour: Red, Black, White, Green Ø = 2.10±0.05mm mm*2	V-75 PVC (AS/NZS 3808 & RoHS) Colour: Red, Black, White, Green Ø = 2.65±0.05mm mm*4
MAXIMUM OPERATING VOLTAGE	300V – as per (UL) E230636 CL3	300V – as per (UL) E230636 CL3	300V – as per (UL) E230636 CL3	300V – as per (UL) E230636 CL3
RIP CORD	Yes	Yes	Yes	Yes
OUTER JACKET	PVC RoHS Flame Retardant (HBZRH-80FZW) PVC Colour: Black	PVC RoHS Flame Retardant (HBZRH-80FZW) PVC Colour: Black	PVC RoHS Flame Retardant (HBZRH-80FZW) PVC Colour: Black	PVC RoHS Flame Retardant (HBZRH-80FZW) PVC Colour: Black
NOMINAL O.D (mm)	Ø = 6.20±0.2mm	Ø = 7.30±0.2mm	Ø = 7.20±0.2mm	Ø = 8.10±0.1mm
CABLE MARKINGS	MASER SPEAKER CABLE MSPK265016 1.3 mm ² 2×65 / 0.16 OXYGEN FREE COPPER RoHS Flame Retardant EXTRA LOW VOLTAGE 001M-100M-250M	MASER SPEAKER CABLE MSPK2105016 2.1 mm ² 2×105 / 0.16 OXYGEN FREE COPPER RoHS Flame Retardant EXTRA LOW VOLTAGE 001M-100M-250M	MASER SPEAKER CABLE MSPK465016 1.3 mm ² 4×65 / 0.16 OXYGEN FREE COPPER RoHS Flame Retardant EXTRA LOW VOLTAGE 001M-100M-250M	MASER SPEAKER CABLE MSPK4105016 2.1 mm ² 4×105 / 0.16 OXYGEN FREE COPPER RoHS Flame Retardant EXTRA LOW VOLTAGE 001M-100M-250M
PACKAGING	100m Reel-in-a-Box / 250m Reel-in-a-Box	100m Reel-in-a-Box / 250m Drum	100m Reel-in-a-Box / 250m Drum	100m Reel-in-a-Box / 250m Drum



Maser Communications products are approved and meet the GREENSTAR “Best Practice PVC” criteria as set out by the Green Building Council of Australia (GBCA). BUREAU VERITAS CoC No:2821 7/8/2019. As part of this commitment to reduce the environmental impact of PVC material, Maser Communications will aid in the process of recycling any of their relevant product that has reached end of life. For further information on this process please contact us.

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.